

1. THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE: Dry pressed ceramic tiles with low water absorption Eb≤0,5%; Annex G, Bla Group, glazed (GL); polished

2. INTENDED USE OR USES: For walls and floors interanal and for walls exteranal, in buildings and industrial facilities.

3. MANUFACTURER: CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce

4. SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE: SYSTEM 4

5. HARMONIZED STANDARD: EN 14411:2012

6. DECLARED PERFORMANCE:

ESSENTIAL CHARACTERISTICS	PERFORMANCE (LEVEL AND/OR CLASS)
Reaction-to-fire performance	A1 / A1 _{FL} Classified Without Testing (CWT)
Release of dangerous substances:	
- Cadmium	≤ 0,07mg/dm ²
- Lead	≤ 0,8mg/dm ²
Breaking strength:	
- thickness ≥7,5mm	≥ 1300 N
Bond strength/adhesion [N/mm²]:	
- cementitious adhesives	≥ 0,5 N/mm ²
- dispersion adhesives	≥ 1 N/mm ²
- reaction resin adhesives	≥ 2 N/mm ²
Slippage according to CEN/TS 16165:2012, Annex B	NPD - No Performance Determined
Thermal shock resistance	Pass
Durability for:	
- internal use:	Pass
- external use: resistance to freeze-thaw cycles	Pass
Tactility	NPD - No Performance Determined

A copy of the Declaration of Performance is available on the website: www.cersanit.com; www.opoczno.eu

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:

Signed on behalf of the manufacturer

Kielce, 01.04.2020

QUALITY SYSTEM MANAGER

Jolanta Grzebna